

# PRODUCT INFORMATION NOTICE



*PIN No:* TEV-36  
*Date:* January 4, 2016  
*By:* Karen Alvarado  
*Issue:* All-Temp<sup>2B</sup> Low Profile Unit Coolers  
*Subject:* All-Temp<sup>2B</sup> Literature Update

The following revisions have been made to ColdZone's All-Temp<sup>2B</sup> Low Profile Unit Coolers literature (CZ-CAX-1215A):

- Updated motor type options to include dual speed EC motors and removed shaded pole motors.
- Added 460V data for PSC motors.
- Expanded nomenclature to include Pre-assembly Codes for pre-configured models that will be stocked in our finished goods warehouses for quicker customer turnaround.
  - Blank = Standard configuration.
  - T = Factory-mounted TXV (only).
  - L = Factory-mounted TXV, LLS, and Mechanical T-Stat.
  - M = Master Configuration with mounted TXV, T-Stat, LLS and copper Tee.

These pre-assembly codes are only for the purpose of identifying finished goods that include optional components. Do not use these codes when ordering units to be built on the production line.

- Changed the Hot Gas Re-Evap designation to "3 pipe defrost." The Re-evaporator/Heat Exchanger (HEA) is no longer available.
- New color palette and graphics.

Please refer to the ColdZone All-Temp<sup>2B</sup> Low Profile Unit Coolers product catalog CZ-CAX-1215A for up-to-date information and available options. The PDF is posted on the website at <http://coldzone.htpgusa.com/images/pdfs/CZ-CAX-1215A2-web.pdf>. Printed copies are not available at this time. We will send notification when printed copies are available to order.

## **ACTION:**

Please contact your representatives and customers of the availability of this update and send them the direct link to the website listed above.

Karen Alvarado  
HTPG Marketing Specialist