

## REFRIGERANT CHARGE REQUIREMENTS

### KRAMER MODEL CSA / CSE / CSG UNIT COOLERS

#### HIGH, MEDIUM & LOW TEMP. REFRIGERANT R-22 & R-404A

<u>EVAP MODEL</u>	<u>R-22; MED.</u> <u>(LB'S.)</u>	<u>R-22; LOW</u> <u>(LB'S.)</u>	<u>R-404A; MED.</u> <u>(LB'S.)</u>	<u>R-404A; LOW</u> <u>(LB'S.)</u>
CSA145	1.83	-	1.62	-
CSA191	2.45	-	2.20	-
CSA240	2.80	-	2.50	-
CSA305	4.60	-	4.12	-
CSA370	5.82	-	5.24	-
CSA415	7.0	-	6.30	-
CSA490	7.0	-	6.30	-
CSA620	10.5	-	9.43	-
CSE130	1.83	1.95	1.62	1.78
CSE150	2.45	2.60	2.20	2.40
CSE185	2.80	2.92	2.50	2.70
CSE270	4.60	4.90	4.12	4.45
CSE320	6.0	6.33	5.34	5.80
CSE385	7.0	7.41	6.30	6.80
CSE460	7.0	7.41	6.30	6.80
CSE520	10.5	11.12	9.43	10.20
CSG130	1.83	1.95	1.62	1.78
CSG150	2.45	2.60	2.20	2.40
CSG185	2.80	2.92	2.50	2.70
CSG270	4.60	4.90	4.12	4.45
CSG320	6.0	6.33	5.34	5.80
CSG385	7.0	7.41	6.30	6.80
CSG460	7.0	7.41	6.30	6.80
CSG520	10.5	11.12	9.43	10.20