

# REFRIGERANT CHARGE REQUIREMENTS

## KRAMER MODEL *LPE / LPG* UNIT COOLERS

### MEDIUM & LOW TEMP. REFRIGERANT *R-22 & R404A*

<u>EVAP MODEL</u>	<u>R-22; MED.</u> <u>(LB'S.)</u>	<u>R-22; LOW</u> <u>(LB'S.)</u>	<u>R-404A; MED.</u> <u>(LB'S.)</u>	<u>R-404A; LOW</u> <u>(LB'S.)</u>
LPE / LPG35	.40	.42	.36	.39
LPE / LPG41	.60	.63	.53	.58
LPE / LPG46	.79	.83	.71	.76
LPE / LPG63	.70	.74	.63	.68
LPE / LPG71	1.10	1.11	.94	1.02
LPE / LPG92	1.60	1.67	1.41	1.53
LPE / LPG120	1.80	1.90	1.60	1.72
LPE / LPG138	2.40	2.50	2.12	2.30
LPE / LPG162	2.40	2.50	2.12	2.30
LPE / LPG184	3.14	3.34	2.83	3.10
LPE / LPG220	3.0	3.13	2.70	2.90
LPE / LPG240	2.40	2.50	2.12	2.30
LPE / LPG265	3.14	3.34	2.83	3.05